DC BATTERY BACKUP BELT DRIVE LED WI-FI® GARAGE DOOR OPENER

Corner to Corner Lighting™ makes the entire garage bright.

AUTOMATIC GARAGE DOOR LOCK CAPABLE

KEY FEATURES

ULTRA-BRIGHT Lighting

QUIET Operation

POWER-OUTAGE Performance

WI-FI Built In

BATTERY BACKUP CALIFORNIA SB-969 COMPLIANT

myQ integrates with leading smart home platforms. Visit myQ.com to learn more.

SECURE

CORNER TO CORNER LIGHTING WITH LONG-LASTING LEDS DELIVERS 3,100 LUMENS OF DAYLIGHT-LIKE LIGHTING TO THE ENTIRE GARAGE SPACE.

AUTOMATIC GARAGE DOOR LOCK CAPABLE: DEADBOLT LOCKS THE GARAGE DOOR, MAKING IT VIRTUALLY IMPENETRABLE (2 MAX., SOLD SEPARATELY).

TIMER-TO-CLOSE CAN BE PROGRAMMED TO CLOSE THE DOOR AFTER A SET AMOUNT OF TIME.

SECURITY+ 2.0® SAFEGUARDS GARAGE ACCESS BY SENDING A NEW CODE WITH EVERY CLICK.

POSILOCK® ELECTRONICALLY PROTECTS AGAINST FORCED OPENINGS.

MOTION DETECTOR LIGHTS THE WAY AUTOMATICALLY.

THE PROTECTOR SYSTEM® INVISIBLE LIGHT BEAM AUTO-REVERSES THE DOOR IF THERE IS AN OBSTRUCTION.

QUIET AND RELIABLE

BELT DRIVE SYSTEM AND QUIET DC MOTOR PROVIDE SMOOTH OPERATION AND LONG-LASTING SERVICE.

SOFT START/STOP FOR SMOOTH OPERATION.

BATTERY BACKUP ENSURES GARAGE ACCESS EVEN WHEN THE POWER'S OUT.

WARRANTY LIFETIME MOTOR, 5-YEAR PARTS, 1-YEAR BATTERY AND ACCESSORIES.

SMART

BUILT-IN WI-FI FOR THE EASIEST WAY TO CONNECT THE GARAGE.

myQ MOBILE APP LETS USERS RECEIVE ALERTS AND CONTROL THE OPENER FROM ANYWHERE.

*Linking your myQ account to a partner may require an additional accessory purchase or subscription fee. Smartphone not included.

INCLUDED ACCESSORIES:

SMART CONTROL PANEL® LCD display enables simple programming and adjustment of settings. — **880LMW**

3-BUTTON REMOTE CONTROL Operates up to 3 openers or myQ Light Accessories. — **893MAX**

INTEGRATED BATTERY BACKUP Powers up the opener when the power's out. — **485LM**

POWERFUL ADD-ONS:

AUTOMATIC GARAGE DOOR LOCK CAPABLE Deadbolts the garage door automatically every time it closes. — **841LM**

myQ HOME BRIDGE Adds Apple® HomeKit™ compatibility and Siri® voice control to Wi-Fi-enabled openers. Installs easily in the garage within Wi-Fi range.** — **819LMB**
Works with Apple HomeKit

REMOTE LIGHT CONTROL Plug in any lamp to this device to control it with a smartphone or garage remote. — **825LM**

MINI UNIVERSAL REMOTE CONTROL Compact and portable to provide quick, easy garage access. — **374UT**

WIRELESS KEYLESS ENTRY Provides convenient, secure access from outside the garage with a 4-digit PIN. — **877MAX**

LiftMaster®

MASTERFUL ENGINEERING.

DC BATTERY BACKUP BELT DRIVE
LED WI-FI® GARAGE DOOR OPENER

MOTOR
- 12V DC
- 53 RPM
- Automatic Thermal Protection
- Permanent Lubrication

POWER
- 120V AC
- 60 Hz Voltage
- 2.7A Current Rating
- UL® Listed
- 6' Power Cord (3-Prong)

MECHANICS
- **Steel Chassis, T-Rail and Trolley**
- **Full Reinforced Belt Drive Mechanism** (63:1 Gear Reduction and Adjustable Door Arm)
- **Auto-Force** Adjustment for Changing Weather and Environmental Conditions
- **Electronic Limits** for Easy Setup
- **DC Wi-Fi Logic Board** with Built-In Surge Suppressor (for Replacement Logic Boards, Order Part 050DCTWFLK)
- **2 Lock Terminals** Allow up to 2 Locks to Be Connected (Sold Separately)

DIMENSIONS

Rail Options	7'	8'	10'
Installed Length	125"	140"	164"
Max. Opening	7'6"	8'6"	10'6"

Headroom Clearance Required: 2"

9" Per second for door to move upward

SPEED

6.5" Per second for door to move downward

STANDARD SPECS.

SECURITY

SECURITY+ 2.0®
RADIO CONTROLS

Operating Range: **~200'**

Operating Temperature: -40°F to 150°F

3-Button Remote Control (893MAX)
- Remote Control: 310, 315 and 390 MHz Tri-Band*
- Garage Door Opener: Frequency Agile on 310, 315 and 390 MHz
- Anti-Burglary Coding

*Tri-band on Security+ 2.0 coding only. Premium remote control is backwards compatible to all LiftMaster® openers manufactured since January 1993.

ENCRYPTED CONTROLS
Smart Control Panel® (880LMW)
- Timer-to-Close
- Program Remote Controls, Keypads and myQ Accessories
- Maintenance Alert System
- Easy Wi-Fi Setup

SMART

myQ® RADIO

902–928 MHz
50-Channel FHSS
(Frequency Hopping Spread Spectrum)

- Provides 2-way communication from garage door opener and myQ Accessories.
- Enables monitoring and control of garage door openers and lighting controls via smartphone, tablet or computer.

HOMELINK® COMPATIBLE (VERSION 4.0 OR HIGHER**)

**May require an external adapter depending on the model and year of your vehicle. Visit HomeLink.com for additional information.

ELECTRICAL

LIGHTING

- 2 LED Light Panels
- 100 Points of LED Light
- 3,100 Lumens,*** 4,000 Kelvin Light Temperature
- Adjustable Time
- Disabled in Battery Backup Mode

***Verified by an independent lab.

SHIPPING.

SHIPPING WEIGHT (in lbs.)

22 HEAD **17** RAIL **3** AUTOMATIC GARAGE DOOR LOCK (OPTIONAL)

CARTONS (3)
CARTON 1: 19.81" x 11.94" x 11.19"
- Garage Door Opener Head (WLED) with Integrated Battery Backup (485LM)
- Smart Control Panel (880LMW)
- 3-Button Remote Control (893MAX)
- The Protector System® Safety Reversing Sensors

CARTON 2: 10'4" x 5" x 5" (for 7' Rail)
- Assembled Solid-Steel Belt T-Rail

CARTON 3 (OPTIONAL): 8" x 4.5" x 4"
- Automatic Garage Door Lock (841LM)

SAFETY AND SECURITY.

- Automatic Garage Door Lock Capable (2 Max.)
- Alert 2-Close/Unattended Close Operation†
- Motion Detection Feature on Control Panel
- Emergency/Quick Release
- Automatic Trolley Reconnect
- Ventilation/Pet Opening
- Down Safety Reverse
- Up Safety Stop
- Safety Beam Obstruction Turns Lights On
- Maintenance Alert System
- Garage Door Opener Capacity of up to 40 Remote Controls, 4 Wireless Keyless Entry Systems and 16 myQ Devices

†WARNING: to reduce the risk of injury to persons—ONLY enable Timer-to-Close and myQ remote operation features when opener is installed on a sectional door.

LiftMaster®