Therma Safe 3200




Formerly marketed as Orion 3200

BETTER Door: Ltd Lifetime Springs: 3 yr Hardware: 4 yr • R-9.0 Thermal Rating • 12 Colors Steel Construction • 6 Panel Designs • 2" Sections • 26 Window Designs **Thermal Rating** Customizations

Low Maintenance

Luxury Level




PANEL DESIGN OPTIONS

 Traditional Country 	2 Ranch4 Cottage	⁵ Flush⁶ Microgroove
1		2

	1

SAFETY, DURABILITY, EFFICIENCY

The Hörmann Therma Safe 3200 is the best choice if you are looking for an affordable insulated garage door. The virtually maintenance-free Therma Safe features a steel front and back with a polystyrene core with an R-value of 9.0. The range of options gives you choices to beautify your home while increasing your savings on energy.



Deep Tongue and 1 Groove

Section joints contribute to the door's excellent strength. Intermediate seals prevent air infiltration, which enhances the insulation properties.

3-Layer Sandwich 2 Construction

Steel front and back construction with insulating polystyrene core increases energy savings and provides a very smooth and quiet operation.

Well-defined Panel 3 Embossments

Easy to clean woodgrain texture, galvanized and finish painted steel provide years of trouble-free performance and beauty.



Hörmann Innovations

FingerGuard[™] Pinch Resistant



The FingerGuard™ section joints and hinges provide an air-tight seal and prevent finger injuries both inside and outside.

Between Section & Side Seals



Factory installed between section weather seals and side seals offer maximum protection from the outside elements while further enhancing the insulation properties of a door.

White 11 Ball Bearing Nylon Rollers



Hörmann nylon rollers feature 11 pre-lubed ball bearings encased in a high strength steel casing that provides a quiet ride and years of reliable service.

WINDOW DESIGN OPTIONS

		2	
1 2 3 4			
	-		
		6	
5 6 7 8		8 8	
9 10 11 12			
		12	
1 White If Teratone 2 Sandstone 7 Black		19 ⁴¹¹¹¹¹ allin allin	allh
3 Almond 8 Hunter Green 4 Desert Tan 9 Golden Oak			φφ.
5 Brown 10 Medium Oak Color application method will be at 11 Walnut	Second Second Second Second		
the discretion of the manufacturer. ¹² Rosewood		₁₈ and and and	
All colors shown as accurately as printing technology allows.			
		20	
	21	22	
	1 Standard Short	2 Standard Long	on-insulated glass.
	³ Cross Short	4 Cross 6 Long	
	5 Cross Arch	⁶ Cross 8 & Cross Arch L	
	7 Stockbridge Short	⁸ Stockbridge & Arch Lo	ng
	9 Prairie Short	10 Prairie Long	
	 Cathedral Short Cascade Short 	12 Cathedral Long14 Cascade Long	
	 Diamond Short 	¹⁶ Diamond Long	
	17 Sherwood Short	¹⁸ Sherwood Long	
	¹⁹ Sunrise Short (4 panels)	²⁰ Sunrise Short (8 panels	;)
	²¹ Sunrise Long (2 panels)	22 Sunrise Long (4 panels))
• • • • •			J.
Call toll freeContactEastern & Central US: 877.654.6762Email: info@hormann.uWestern US: 800.522.2264Website: hormann.us	JS	SIDA. Member of DASMA International Action of the Control of th	USGBC
Canada: 833.743.2443	F	Follow us on social media	MEMBER
	ſ		
AVAILABLE FROM:		Ó	in
		J'RMAN	

We reserve the right to change specifications without notice. ©Hörmann (28/04/2023)